

WATER TO GO

MASTER/SLAVE

WATER, WILL REFRESHES YOUR OFFER.

Filtered water dispenser connected directly to mains water. The module can be easily installed by completing the Vending Solutions offer with an additional service highly appreciated by user and very simple to use: one touch to choose between still or sparkling fresh water and fill a flask/glass with clean and controlled water.



WATER TO GO MODULE MASTER
STICKER KIT WITH "DESIGN YOUR BREAK" GRAPHIC (OPTIONAL)



LEI600 PLUS 2CUPS + WATER TO GO MODULE SLAVE

USER INTERFACE

- Elegant design with the door frame in anodized aluminum.
- Distribution area that allows the use of containers of up to 220 mm in height, and which lights up for the product removal
- Slow descent sliding door.
- Suitable for use by minors or disabled people in accordance with current regulations.

MASTER VERSION

- Touch: 7" touchscreen display customisable.
- Anti-vandalism coin insertion.

SLAVE VERSION

- Slave version works together with a hot drinks equipped with a Touchscreen display.
- Selection takes place via a touch-screen menu with the possibility of choosing between still or sparkling fresh water.

SPECIFICATIONS

- ELECTRICAL SUPPLY: 230 Vac – 50 Hz
- POWER SUPPLY: 200 W
- TEMPERATURE OF DISTRIBUTED WATER: approximately 8° C
- COOLING UNIT: 1/6 HP one single unit
- REFRIGERANT GAS: R 134 A

FEATURES

- This module allows the utmost flexibility in installation in accordance with the requirements of the chosen location.
- Sensor to detect the presence of a glass/flask.
- Incoming water pressure regulation with pressure gauge.
- Volume meters for incoming and distributed water.
- Sampling tap for the taking of samples for Health and Safety inspections.

Sparkling water:

- Set-up for connection to a CO₂ tank of up to 10 kg via dedicated connector.

- Safety lock for the gas tank.
- Adjustment of incoming CO₂ pressure for the gas system.

Disinfection and debacterization:

- 16 W UV lamp for incoming water.
- 4.5 + 4.5 W lamp for distributed water.

Filtration, reduction of chemical pollutants and unpleasant odours:

- Composite filter cartridge supplied.
- Possibility to fit a second unit for the water filter to use as a water softener.

ACCESSORIES

- Water module sanitisation kit.
- Motorised door kit.
- Cup holder kit.
- Dual sensor kit (required for cup holder kit).

WATER TO GO MODULE	W2GOSL01BV	W2GOMA01BV
VERSION	SLAVE	MASTER
TEMPERATURE OF DISTRIBUTED WATER	~ 8° C	~ 8° C
AVERAGE DISTRIBUTABLE VOLUME	60 l/h	60 l/h
DISTRIBUTION SPEED	still water: 0.5 lt in 20 s sparkling water: 0.5 lt in 15 s	still water: 0.5 lt in 20 s sparkling water: 0.5 lt in 15 s
CO ₂	max 10 kg	max 10 kg
DIMENSIONS MM	1830H x 450W x 920W / WEIGHT 165 KG	1830H x 450W x 920W / WEIGHT 170 KG